

- Integrated Circuits in RF Systems, p.19-22.
<https://doi.org/10.1109/SIRF.2018.8304218>
- Ciocoveanu R, Weigel R, Issakov V, 2019a. A highly integrated 60 GHz receiver for radar applications in 28 nm bulk CMOS. Proc IEEE International Conf on Microwaves, Antennas, Communications and Electronic Systems, p.1-5.
<https://doi.org/10.1109/COMCAS44984.2019.8958434>
- Ciocoveanu R, Weigel R, Hagelauer A, et al., 2019b. Modified gilbert-cell mixer with an LO waveform shaper and switched gate-biasing for $1/f$ noise reduction in 28-nm CMOS. *IEEE Trans Circuits Syst II: Express Briefs*, 66(10):1688-1692.
<https://doi.org/10.1109/TCSII.2019.2923595>
- Cui J, LI PP, Sheng WX, 2023. High linearity U-band power amplifier design: a novel intermodulation point analysis method. *Front Inform Technol Electron Eng*, 24(1):176-186.
<https://doi.org/10.1631/FITEE.2200082>
- Duan ZM, Wu BW, Wang Y, et al., 2023. A 76-81 GHz 2×8 MIMO radar transceiver with broadband fast chirp generation and 16-antenna-in-package virtual array. *IEEE J Solid-State Circuits*, 58(11):3103-3112.
<https://doi.org/10.1109/JSSC.2023.3272676>
- Inanlou F, Coen CT, Cressler JD, 2014. A 1.0 V, 10-22 GHz, 4 mW LNA utilizing weakly saturated SiGe HBTs for single-chip, low-power, remote sensing applications. *IEEE Microwave Wireless Compon Lett*, 24(12):890-892.
<https://doi.org/10.1109/LMWC.2014.2361662>
- Kashani MH, Tarkeshdouz A, Afshari E, et al., 2019. A 53-67 GHz low-noise mixer-first receiver front-end in 65-nm CMOS. *IEEE Trans Circuits Syst I: Regul Pap*, 66(6):2051-2063.
<https://doi.org/10.1109/TCSI.2019.2895883>
- Kim SK, Cui CL, Huang GC, et al., 2012. A 76 GHz low LO power mixer with a split self-driven switching cell in 65 nm CMOS technology. *IEEE Microwave Wireless Comp Lett*, 22(9):480-482.
<https://doi.org/10.1109/LMWC.2012.2213076>
- Kolios V, Kalivas G, 2016. A 60 GHz down-conversion mixer with variable gain and bandwidth in 130 nm CMOS technology. Proc 5th International Conf on Modern Circuits and Systems Technologies, p.1-4.
<https://doi.org/10.1109/MOCAS.2016.7495147>
- Krishnamurthy S, Iotti L, Niknejad AM, 2021. Design of high-linearity mixer-first receivers for mm-wave digital MIMO arrays. *IEEE J Solid-State Circuits*, 56(11):3375-3387.
<https://doi.org/10.1109/JSSC.2021.3101984>
- Liu ZQ, Dong JY, Chen ZL, et al., 2018. A 62-90 GHz high linearity and low noise CMOS mixer using transformer-coupling cascode topology. *IEEE Access*, 6:19338-19344.
<https://doi.org/10.1109/ACCESS.2018.2814062>
- Longhi PE, Pace L, Colangeli S, et al., 2020. V-band GaAs metamorphic low-noise amplifier design technique for sharp gain roll-off at lower frequencies. *IEEE Microwave Wireless Compon Lett*, 30(6):601-604.
<https://doi.org/10.1109/LMWC.2020.2986927>
- Mazor N, Sheinman B, Katz O, et al., 2017. Highly linear 60-GHz SiGe down-conversion/up-conversion mixers. *IEEE Microwave Wireless Compon Lett*, 27(4):401-403.
<https://doi.org/10.1109/LMWC.2017.2678426>
- Razavi B, 2000. Design of Analog CMOS Integrated Circuits. New York: McGraw-Hill.
- Sutbas B, Ng HJ, Wessel J, et al., 2022. A V-band low-power and compact down-conversion mixer with low LO power in 130-nm SiGe BiCMOS technology. Proc 16th European Microwave Integrated Circuits Conf, p.96-99.
<https://doi.org/10.23919/EuMIC50153.2022.9783953>
- Vardarli E, Sakalas P, Schröter M, 2022. A 5.9 mW E-/W-band SiGe-HBT LNA with 48 GHz 3-dB bandwidth and 4.5-dB noise figure. *IEEE Microwave Wireless Compon Lett*, 32(12):1451-1454.
<https://doi.org/10.1109/LMWC.2022.3192488>
- Wang RT, Zhu W, Wang Y, 2024. An adaptive analog temperature compensated W-Band front-end with ± 0.0033 dB/ $^{\circ}$ C gain variation across-30 $^{\circ}$ C to 120 $^{\circ}$ C. *IEEE Trans Circuits Syst II: Express Briefs*, 71(2):542-546.
<https://doi.org/10.1109/TCSII.2023.3313815>
- Wei HJ, Meng CC, Wang TW, et al., 2012. 60-GHz dual-conversion down-/up-converters using Schottky diode in 0.18 μ m foundry CMOS technology. *IEEE Trans Microwave Theory Tech*, 60(6):1684-1698.
<https://doi.org/10.1109/TMTT.2012.2189412>
- Wu CL, Yu CK, Kenneth K O, 2015. Amplification of non-linearity in multiple gate transistor millimeter wave mixer for improvement of linearity and noise figure. *IEEE Microwave Wireless Compon Lett*, 25(5):310-312.
<https://doi.org/10.1109/LMWC.2015.2409784>
- Yu YM, Kang K, 2020. Analysis and design of transformer-based CMOS ultra-wideband millimeter-wave circuits for wireless applications: a review. *Front Inf Technol Electron Eng*, 21(1):97-115.
<https://doi.org/10.1631/FITEE.1900491>
- Yu YM, Liu RY, Zuo YJ, et al., 2024. A 60-90 GHz mixer-first receiver with adaptive temperature-compensation technique. *IEEE Microwave Wireless Technol Lett*, 34(4):443-446.
<https://doi.org/10.1109/LMWT.2024.3369652>